VCBS-DUAL HEAD VERTICAL CONVEYORIZED BAND SEALING SYSTEM FOR SLIDER BAGS



- Dual Head Vertical Rotary Band Sealing System with Synchronized Conveyor is designed to make two seals on the bag in one pass through the machine. Built-in feed guides allow operators to properly place the bags to be sealed in the target area.
- Single head systems available for bags without the tamper evident upper seal.
- System is designed to seal slider zipper style premade bags below and above the slider. The first seal head seals the slider to the outer layer followed by the second head which seals the tamper evident portion above the slider.
- Supplied with Lower Carry Belts and interfaced Variable Speed Conveyor, 6" wide x 8' long with fully adjustable stainless steel Guide Rails. Independent height adjustable seal heads allow flexibility for various size bags. Optional 12" wide lower conveyor belt available.
- Variable speeds up to 540 inches per minute (45 fpm).
 Please note that all bags may not seal at this speed.
 Production speeds of 15 to 20 bags per minute are achievable. Actual sealing speed is dependent on structure and thickness or material being sealed.
- No compressed air required.

- Each head is designed with dual 5" long heating zones and dual 5" long cooling zones for greater flexibility in product sealing of difficult thickness materials with temperatures up to 450 degrees Fahrenheit.
- Quality seals of 3/8" or 1/2" wide are achieved through the use of special heavy duty wear-resistant laminated Teflon or Kevlar sealing bands
- Hard Chrome plated sealing bars followed by Nickel plated cooling bars allow for maximum wear resistance.
- Digital Temperature Controls maintain consistent heat and assures quality hermetic seals.
- Fully synchronized speed control system guarantees speed match between the heads and the conveyor.
 Simple one speed dial changes all motor speeds.
- Optional Roller Infeed Conveyor (shown) can act as a staging area for bags to be sealed.
- Electrical 110 VAC 15 amps/ 60 Cycle. 220 volt supply available as an option.
- Custom configurations are available, inquire with our Sales Department about your application.

OVER 60 YEARS OF SUCCESSFUL PACKAGING EXPERIENCE



ALL PACKAGING MACHINERY, CORP.